

Experience-based innovation

Neuson Forest has represented high-quality forestry technology "Made in Austria" for decades.

Our robust and compact tracked machines are specially designed for professional use in the most difficult conditions, **even on slopes of up to 145%,...**



or in **swamps and wetlands.**



With a focus on **efficiency, soil protection and safety,** we set new standards in forestry.

Our processors work flexibly and stably on any terrain thanks to their **360-degree rotation,** and can be optimally adapted to individual requirements thanks to different weight categories, crane lengths, chain configurations and the independent choice of processor head brand.



Comfort combined with safety.

The spacious driver's cab offers optimal panoramic visibility, ergonomic handling, heating and air conditioning to work focused in any weather condition.

The **FOPS, ROPS and OPS** certified cabin meets the highest safety standards worldwide, even in the harshest conditions.

Well-**designed service** platforms complete the concept.



Information subject to change and possible printing errors.



Neuson Forest GmbH
Freilinger Straße 40 A-4614
Marchtrenk
www.neuson-forest.com



Importer and distributor in Spain
www.forestpioneer.com





Neuson 154 HVT

Compact and powerful all-terrain processors for clearing and marshy areas

129 kW / 175 HP

Two hydraulic pumps

655 l of total flow

Reversible fan.

Cutting diameter up to 65 cm.

Cabin corrector.

(25° forward / 15° lateral)

Crane reach 10 m (11 m optional)

Transport width only 2500 mm*

Transport height LESS THAN 3200 mm

Track overhang turned 90° to one side: 340 mm

Turning radius 2275 mm

Base machine weight 15.8 t

RECOMMENDED HEAD: **AFM 45**

Neuson 204 HVT

All-terrain processors for thinning and selective harvesting, or for final cutting of wood affected by pests and storms

163 kW / 222 HP

AXKO LS/P hydraulic pump — 399 l/min

Reversible fan

Cutting diameter up to 72 cm

Slope compensation

(25° forward / 15° lateral)

Crane reach 10.3 m

(11.5 m optional)

Transport width only 2,500 mm

(2,700 mm*)

Transport height from 3,200 mm

(3,400 mm*)

Track overhang turned 90° to one side: 305 mm

(205 mm*)

Base machine weight 20.7 t

*with wide running gear

RECOMMENDED HEAD: **AFM 55**

Neuson 264 HVT

Processors for final cuts with processing heads up to 900 mm, or for thinning with a range of up to 15 meters

226 kW / 307 HP

AXKO LS/P hydraulic pump — 530 l/min

Reversible fan

Cutting diameter up to 90 cm

Cabin corrector

(25° forward / 15° lateral)

Crane reach 9 m

(optional: 10, 12 and 14.5 m)

Transport width only 2,950 mm*

Transport height from 3,535 mm

Track overhang turned 90° to one side: 200 mm

Base machine weight 26.5 t

*with standard chains

RECOMMENDED HEAD: **AFM 65**